

Fraises à ébavurer

Fraise à ébavurer / noyer 3 dents 90° HSS



Nombre de dents : 3
Angle : 90°
Norme : DIN 335C

- Fonte
- Acier doux / mi-dur
- Acier dur
- Inox
- Aluminium

- Adapté
- Utilisation occasionnelle
- Inadapté

Ø	Long. tot.	Ø queue	Capacité vis	Vitesse en Tr/min		Référence
				Acier	Inox	
4.3	40	4	M2	1100	880	A820.043
5.0	40	4	M2 - M2.5	950	765	A820.050
5.3	40	4	M2.5	900	720	A820.053
5.8	45	5	M3	820	650	A820.058
6.3	45	5	M3	750	600	A820.063
7.3	50	6	M3.5	650	520	A820.073
8.0	50	6	M3.5	580	475	A820.080
8.3	50	6	M4	570	460	A820.083
10.0	50	6	M4	475	380	A820.100
10.4	50	6	M5	450	360	A820.104
11.5	56	8	M5	420	330	A820.115
12.4	56	8	M6	380	300	A820.124
15.0	60	10	M6	320	250	A820.150
16.5	60	10	M8	290	230	A820.165
19.0	63	10	M8	250	200	A820.190
20.5	63	10	M10	230	185	A820.205
23.0	67	10	M10	210	160	A820.230
25.0	67	10	M12	190	150	A820.250
28.0	71	12	M14	170	130	A820.280
31.0	71	12	M16	150	120	A820.310
40.0	80	15	M24	120	90	A820.400

Description	Ø	Réf.
Coffret 6 Fraises à ébavurer 3 dents 90° HSS	Ø6.3-8.3-10.4-12.4-16.5-20.5	A820V1
Coffret 7 Fraises à ébavurer 3 dents 90° HSS	Ø6.3-8.3-10.4-12.4-16.5-20.5-25.0	A820V2

Fraises à ébavurer

Fraise à ébavurer / noyer 3 dents 90° HSS cobalt 5%

Nombre de dents : 3
Angle : 90°
Norme : DIN 335C

- Fonte
- Acier doux / mi-dur
- Acier dur
- Inox
- Aluminium

- Adapté
- Utilisation occasionnelle
- Inadapté



Ø	Long. tot.	Ø queue	Capacité vis	Vitesse en Tr/min		Référence
				Acier	Inox	
6.3	45	5	M3	750	600	A828.063
8.3	50	6	M4	570	460	A828.083
10.4	50	6	M5	450	360	A828.104
12.4	56	8	M6	380	300	A828.124
16.5	60	10	M8	290	230	A828.165
20.5	63	10	M10	230	185	A828.205
25.0	67	10	M12	190	150	A828.250
31.0	71	12	M16	150	120	A828.310

Description	Ø	Réf.
Coffret 6 Fraises à ébavurer 3 dents 90° HSS cobalt 5%	Ø6.3-8.3-10.4-12.4-16.5-20.5	A828V1
Coffret 7 Fraises à ébavurer 3 dents 90° HSS cobalt 5%	Ø6.3-8.3-10.4-12.4-16.5-20.5-25.0	A828V2